

3000, 4000 & 5000-Watt Gasoline

This portable generator provides dependable power for homeowners seeking a reliable electrical backup yet is powerful enough for most industrial and contractor needs. It features a large low-tone muffler for quiet operation and a low profile compact design.

All Models Feature

Engine

- Low-oil shutdown engine

Alternator

- Total harmonic distortion (THD) less than 5%
- 100% copper windings

Frame

- Heavy-duty wraparound frame with 1-inch powder coated steel tubing
- Low profile, compact design
- Angled isolator design features four neoprene isolators

Components

- Large low-tone mufflers to reduce noise to lowest level possible
- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Fuel shut-off valve
- Heavy-duty industrial air cleaners hold up under extreme conditions

Miscellaneous

- USDA/USFS-approved spark arrestors
- Circuit breaker protected

GEN-3000-1MH0 Model Additional Features

Alternator

- Brushless 120V alternator

Components

- Large fuel tank capacity for extended run time


GEN-4000 & GEN-5000 Model Additional Features

Alternator

- Brushless 120V/240V alternator



GEN-5000-OMS0



GFCI 5-20R



NEMA L14-20R
125/250V



NEMA L5-30R
125 VAC



CSA
CERTIFIED

Components

- Easy-to-read fuel gauge
- Full power switch
- Fuel tanks are powder coated outside, zinc-plated inside to prevent rusting

Warranties on All Models

2 YEAR LIMITED ALTERNATOR WARRANTY
3 YEAR LIMITED HONDA ENGINE WARRANTY
3 YEAR LIMITED KOHLER ENGINE WARRANTY
3 YEAR LIMITED SUBARU ENGINE WARRANTY

NEW KOHLER ENGINE MODEL

Model Number	GEN-3000-1MH0	GEN-4000-0MH0 / GEN-4000-OMS0	GEN-5000-0MK0 / GEN-5000-OMS0
Max. AC Output	3000 watts	4000 watts	5000 watts
Rated AC Output	2450 watts	3500 watts	4400 watts
Displacement/Engine	163cc Honda OHV	242cc Honda OHV / 211cc Subaru OHC	277cc Kohler OHV / 287cc Subaru OHC
Frequency/Voltage	60Hz/120V	60Hz/120V/240V	60Hz/120V/240V
Max. Amps (120V/240V)	25.0	33.3/16.7	41.7/20.8
Cont. Amps (120V/240V)	20.4	29.2/14.6	36.7/18.3
Receptacles	120V, 20A GFCI duplex	(2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock 120V, 30A twist lock	(2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock 120V, 30A twist lock
Main Circuit Breakers	20A push-button	(2) 20A toggle circuit breaker, single pole 20A toggle circuit breaker, double pole 30A toggle circuit breaker, single pole	(2) 20A toggle circuit breaker, single pole 20A toggle circuit breaker, double pole 30A toggle circuit breaker, single pole
Rated Speed	3600 RPM	3600 RPM	3600 RPM
Decibel Rating	74.8	75.7 / 74.0	73.8
Fuel Capacity	2.6 gallons	5.7 gallons	5.7 gallons
Run Time (at full load)	7.4 hours	9.3 hours	6.8 hours
Dimensions (LxWxH)	25in.x18in.x18in.	29in.x19.75in.x22.5in.	29in.x19.75in.x22.5in.
Ship Wt.	146 lbs.	164 / 168 lbs.	198 lbs.
Net Wt.	130 lbs.	142 / 146 lbs.	176 lbs.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

ACCESSORIES & OPTIONS

Part Number	Description	Fits Models
32-0915	RV generator adapter - 30A/125V female/male; use to connect RV cordsets to 30A generators	4000 & 5000-watt models
AW-5090-0003	Lifting hook - For easier portability, folds down and out of the way when not in use	4000 & 5000-watt models
AW-5740-0009	Wheel kit - For easier portability, pneumatic tires with tubes, rubber gripped handles	4000 & 5000-watt models
GX-0004	Hour meter - Displays number of hours the unit has been in operation	4000 & 5000-watt models
TX-1002-W	Puncture-proof tires - Tires are flat-free, maintenance-free, 10-inch, white hub, two tires	4000 & 5000-watt models